



TRIME®

Lighting Towers

TRIME.RU



LED TECHNOLOGY

2400 sqm

Area illuminated



Parking area



Construction & work sites



Gas, oil & mining operations




Special events



Military applications

HYBRID Line

Operation: **HYBRID**
 fuel tank capacity 42 litres
 batteries AGM -2x24Vdc 130ah
 solar panel 330 W

X-TS


4X100W LED - 8M

T-ZERO PRO

X-TS

4x100W LED - 8M

T-ZERO PRO



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- **Electric tilting head**
- 6 sections manual vertical tower 8,0 m
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 80 km/h
- 4 height adjustable stabilizers
- **No. 2 Batteries AGM 24 Vdc 130 Ah**
- Electric light Tilting
- Emergency stop button
- Timer
- Light sensor
- Solar panel built-in
- DSE 3110

REDUCTION
CO² emissions

REDUCE COSTS
SAVE MONEY

RUNNING TIME
from battery
10 H

RUNNING TIME
before refill
183 h
Fuel Tank capacity 300 L

REDUCTION
noise

REDUCTION
smell

SOLAR PANEL 330W

2400 sqm
area illuminated

22 units
per truck

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
		1180x1340x2670 (LxWxH)		2350x2540x8000 (LxWxH)		853	
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)		
	Led	100W	4	65	2400		
Mast	Lifting method	Max Height	Max Wind Speed				
	Hydraulic	8 m	110 km/h				
Battery Pack	Type	Batteries number	Power Battery pack	Expected battery cycle	Battery life time		
	AGM	2	24 Vdc 130 ah	500	9500 h		
Hybrid Mode	Running time from battery	Running time before refill	Charging time with floodlight off	Complete discharge/charge cycle	Hybrid mode consumption		
	10 h	183 h	9 h	19 h	0,23 l/h		
Solar Panel	Power	Type	Solar panel number				
	330 W	X-Chros Sunerg	1				
Generator	Model	Rated Output	Rated frequency	Rated Voltage			
	Linz SP 10M	4,2 Kva	50 Hz	230 V			
Engine	Type	Number of cylinder	Displacement	Engine speed	Fuel tank capacity (l)	Fuel consumption (l/h)	Cooling system
	Yanmar L70AE	1	320 cm ³	3000 rpm	42	0,5	air



ЛЕГИОН-ТЕХНО
профессионализм - дело техники

Эксклюзивный официальный дистрибьютор
TRIME на территории России и СНГ

trime.ru | info@trime.ru

+7 (929) 653-13-37 | +7 (495) 741-89-01
8 (800) 222-51-05 | +7 (495) 532-37-34